

# G1750P

# Eye/Face Washes

**G1750P** Eye/Face Wash, Wall Mounted, Plastic Bowl



**Application:** Eye/face wash for wall mounting. Two large FS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes and face.

**Spray Head Assembly:** Two FS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

**Valve:** 1/2” IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and Teflon® seals.

**Bowl:** 11 1/2” diameter orange ABS plastic.

**Mounting:** Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

**Supply:** 1/2” NPT female inlet.

**Waste:** 1 1/4” NPT female outlet.

**Sign:** ANSI-compliant identification sign.

**Quality Assurance:** Unit is completely assembled and water tested prior to shipment.

## Available Options

- DC** Stainless steel dust cover for each spray head.
- GRN** Green ABS plastic bowl.
- YEL** Yellow ABS plastic bowl.
- HS** Auxiliary hand-held drench hose for rinsing eyes, face or body.
- SC** Self-closing ball valve.  
*Note: Eye/face washes with self-closing valves do not comply with ANSI Z358.1 - 2004.*
- T** Chrome plated brass tailpiece and trap with 1 1/2” IPS waste connection.
- TP** 1 1/2” OD Chrome plated brass tailpiece.
- TMV** G3600 thermostatic mixing valve precisely blends hot and cold water to deliver warm (tepid) water as provided by ANSI Z358.1-2004. Refer to “Tempering Units” section for complete technical and product selection information.



ETL Listed 101496.  
Units have been tested  
to and comply with  
ANSI Z358.1 - 2004

## GUARDIAN EQUIPMENT

660 North Union Street  
Chicago, IL 60610  
info@gesafety.com

Phone 312 733 2626  
Fax 312 733 4684  
gesafety.com