

G1991

Safety Stations with Eye Wash

G1991 Safety Station with Eye Wash, All-Stainless Steel Construction

Application: All-stainless steel combination eye wash and shower safety station. Stainless steel construction is ideal for highly corrosive environments and clean room applications. Two GS-Plus™ spray-type outlet heads deliver a flood of water for rinsing eyes.

Shower Head: 10" diameter stainless steel.

Shower Valve: 1" IPS Type 316 stainless steel stay-open ball valve. Valve has stainless steel ball and Teflon® seals. Furnished with stainless steel actuating arm and 29" stainless steel pull rod.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Eye Wash Bowl: 11 1/2" diameter stainless steel.

Eye Wash Valve: 1/2" IPS Type 316 stainless steel stay-open ball valve. Valve has stainless steel ball and Teflon® seals.

Pipe and Fittings: Schedule 40 Type 304 brushed stainless steel. Furnished with orange polyethylene covers for vertical piping for high visibility and corrosion resistance.

Supply: 1 1/4" NPT female top or side inlet.

Waste: 1 1/4" NPT female outlet. Outlet can be positioned at either 8" or 20" above finished floor by reversing lower pipe nipples.

Sign: Furnished with ANSI-compliant identification sign.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.

Available Options

- BC** Stainless steel cover for eye wash wash bowl.
- FC20** Regulates shower flow rate to 20 GPM.
- AP275-100 Electric Light and Alarm Horn**
Light and alarm horn summon assistance when eye wash or shower is activated.
- AP250-015 Modesty Curtain**
Modesty curtain for mounting on safety station.
- TMV** G3800 thermostatic mixing valve precisely blends hot and cold water to deliver warm (tepid) water as provided by ANSI Z358.1-2004.



ETL Listed 101496.
Units have been tested
to and comply with
ANSI Z358.1 - 2004

GUARDIAN EQUIPMENT

660 North Union Street
Chicago, IL 60610
info@gesafety.com

Phone 312 733 2626
Fax 312 733 4684
gesafety.com