

IBC-Lines

ECOLINE
Standard-IBC

PALLETS

Basic:

timber pallet, stackable
(heat treated on request)



Upon Request:

plastic runner
12/10



plastic runner
12/08



full-steel frame
12/10



full-steel runner
12/08



combination frame
12/10



CAPACITIES

ECOLINE IBC

- 1000 litres
- 800 litres
- 600 litres

VALVES

basic version: 50 mm fixed, ◆

Volume/litres	Ø mm	detach-		
		fixed	able	gasket
600	50	◆	◆	◆
800	80	◆	◆	◆
1000	50C	◆	◆	◆

◆ PE-CP ◆ EPDM ◇ Viton C: Camloc

DIMENSIONS (LxWxH)

ECOLINE 1000 I

1.200 x 1.000 x 1.165

ECOLINE 800 I

1.200 x 1.000 x 990 oder

ECOLINE 800 I EURO

1.200 x 800 x 1.165

ECOLINE 600 I

1.200 x 800 x 990

WEIGHTS

ECOLINE IBC

Volume (litres)	Weight (kg) – on pallets:			
	wood	plastic	steel	combi
600	56	49	59	✗
800	62	52	52	47
800 EURO	64	54	58	✗
1000	67	55	55	50

LABEL PLATES (mm)

722 x 350	522 x 350
1000 I, 800 I	800 I EURO, 600 I

MATERIALS

Inner Receptacle (Bottle)

- blow moulded HDPE
- colour: natural
- bevelled edges
- colour on request:
black (carbon black)
white (TiO₂)



Outer Frame

- welded tubular steel frame
- galvanized

CERTIFICATIONS

- non UN
- maximum density 1.6

FILLING OPENINGS

basic version:

- 150 mm
- 225 mm
- DAE, Ventix
- 400 mm, sealable clamping ring lid

DYNAMIC LOAD

Stacking height according to specific gravity of product

- more than 1.4: 1-high
- up to 1.4: 2-high



STATIC LOAD

- 4 high
- max. density 1.6



SIDE PLATE (mm)

605 x 350
upon request