

**Product name: EcoSorb Absorbent Rolls and Mats**

**Supplier: DENIOS AG**  
 Dehmer Str. 58-66  
 D-32549 Bad Oeynhausen  
 Tel. 0800 753-0002

**Technical specifications**

**Characteristics**

- absorbs many times its own weight and stores well liquids without dripping
- is durable and hard wearing, easy to handle
- leaves no residue
- ecological: is at least 75% recycled cellulose, a renewable raw material
- low material consumption due to high suction power and absorption capacity

**Area of application**

Oils, coolants, solvents, water and other non-aggressive liquids

**Composition**

75-80% Cellulose (recycled)  
 10-13% Polypropylene/Polyethylene  
 10-13% Flame retardant

**Product description**

<i>Criteria</i>	<i>Mats</i>	<i>Rolls 72 cm</i>	<i>Rolls 36 cm</i>
Article number	201675	201676	201677
Total length	380 mm	38 m	38 m
Total width	480 mm	720 mm	360 mm
Colour	Gray	Gray	Gray

**Packaging**

<i>Criteria</i>	<i>Mats</i>	<i>Rolls 72 cm</i>	<i>Rolls 36 cm</i>
Pack unit	100 mats	1 roll	2 rolls
Dimensions packaging W x D x H (mm)	508 x 406,50 x 585	501,60 x 501,60 x 750	501,60 x 501,60 x 750

**Physical characteristics**

<i>Criteria</i>	<i>Mats</i>	<i>Rolls 72 cm</i>	<i>Rolls 36 cm</i>
Basis weight/grammage	376 gr/m <sup>2</sup> ± 7 %	376 gr/m <sup>2</sup> ± 7 %	376 gr/m <sup>2</sup> ± 7 %
Thickness	6-7 mm	6-7 mm	6-7 mm
Oil absorption capacity (litre per pack)	105	160	160
Water absorption capacity (litre per pack)	77	115	115
Auto ignition temperature	> 250° C (> 482° F)	> 250° C (> 482° F)	> 250° C (> 482° F)

**Important: Not recommended for use with strong acids or caustics.**